

ARENA Sconce
3-5014-xx

oxygen

FIXTURE TYPE _____
PROJECT _____

LOCATION _____
DATE _____




-6 White



-15 Black

LIGHT SOURCE (1x) 14W LED Array, 3000K, 90 CRI (Ra)
LUMINAIRE POWER 12.92W (BLACK finish, 12.98W (WHITE finish)
RATED LIFE (L70) 50000 hrs RL
COLOR TEMPERATURES Field Selectable 3000K/3500K/4000K
 Note: Oxygen Standard setting is 3000K
LUMEN OUTPUT 966.8 Lm (LM-79) WHITE Finish
 728.8 Lm (LM-79) BLACK Finish
INPUT VOLTAGE 120V
DRIVER OUTPUT 350mA, 17W max.
DIMMING TRIAC and ELV dimming at 120V AC
CONSTRUCTION Powder Coated Steel
DIFFUSER - Matte White Etched Acrylic
FINISHES -15 Black, -6 White
MOUNTING 4" Octagonal J-Box
STANDARDS cETLus Damp Listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

W: 8"
H: 11.25"
Ext: 4"
M.C: 8" From top of fixture

Order example for standard fixture:
3-5014-15 (x-xxx: LED Sequence # / -xx: Finish)

