

SABRE Pendant
3-6005-xx

oxygen

FIXTURE TYPE _____

LOCATION _____



-15 Black




-40 AGB

LIGHT SOURCE	(5x) 5.5W LED Array, 3000K, CRI 90
LUMINAIRE POWER	26.71W
RATED LIFE (L70)	50000 hr RL
OPTIONAL COLOR TEMPERATURES	Field Selectable 3000K/3500K/4000K Note: Oxygen Standard setting is 3000K
LUMEN OUTPUT	1121.5 Lm (LM-79)
INPUT VOLTAGE	120V
DRIVER OUTPUT	700 mA, 33W max.
DIMMING	TRIAC and ELV dimming at 120V AC
CONSTRUCTION	Painted Black Steel, Plated Steel
DIFFUSER	- Matte White Acrylic
FINISHES	-15 Black, -40 AGB
MOUNTING	4† Octagonal J-Box
STANDARDS	cETLus Damp Listed, ADA Compliant, Conforms to UL STD 1598, Certi-ed CAN/CSA STD C22.2 No 250.0.

DIMENSIONS

Canopy Dims.: 15 75† Dia.x 1.4† ht
Fixture Dia.: 1.5†
Fixture Ht: 16†
OAH: Provided with 10" Adjustable Cable to Customize hanging Height



Order example for standard -xture:
3-6005-15 (x-xxx: LED Sequence # / -xx: Finish)

