

PALILLOS 10LT LED Pendant
3-803-xx

oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____





-15 Black



-40 AGB

- LIGHT SOURCE** (12) X 3.5W LED Array, Selectable Color Temp, CRI 90
- LUMINAIRE POWER** TBD Input Power
- RATED LIFE** 50000 hr RL
- OPTIONAL COLOR TEMPERATURES** Selectable **(CCT)** 3000/3500/4000K
- LUMEN OUTPUT** TBD
- INPUT VOLTAGE** 120V
- DRIVER OUTPUT** TBD
- DIMMING** TRIAC and ELV dimming at 120V AC
- CONSTRUCTION** Cold Rolled Steel Housing
- DIFFUSER** - Matte White Acrylic
- FINISHES** -15 Black, -40 AGB
- MOUNTING** 4" Octagonal J-Box
- STANDARD** ETL Damp Listed, ADA Compliant, Conforms to UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

H:
Ext:
M.C: X" From top of fixture

Note:

Order example for standard fixture:
3-803-15 (x-xxx: LED Sequence # / -xx: Finish)

