

ALARUM Sconce
3-594-xx

oxygen

FIXTURE TYPE _____
PROJECT _____

LOCATION _____
DATE _____




-15 Black



-24 SN

LIGHT SOURCE	(2x) 4W LED Array, 3000K, 90 CRI (Ra)
LUMINAIRE POWER	7.5W
RATED LIFE (L70)	50000 hr RL
OPTIONAL COLOR TEMPERATURES	3000K Only
LUMEN OUTPUT	378.2 Lm (LM-79)
INPUT VOLTAGE	120V
DRIVER OUTPUT	180 mA 7W max.
DIMMING	TRIAC or ELV dimming at 120V AC Only. Dimmer not Included
CONSTRUCTION	Painted Black Steel, Nickel Plated Steel
DIFFUSER	- Clear/Frost K9 crystal diffusers
FINISHES	-15 Black, -24 SN, -40 AGB
MOUNTING	4† Octagonal J-Box
STANDARDS	cUL Damp Listed, ADA Compliant, Conforms to UL STD 1598, Certi-ed CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

W:	5.5†
H:	8†
Ext:	4†
M.C:	4† From top of -xture

Order example for standard -xture:
3-594-15 (x-xxx: LED Sequence # / -xx: Finish)

