


quorum



Windmill 52-in Galvanized Indoor/ Outdoor Ceiling Fan (10-Blade)

195210-9

HEIGHT CHART



FAN HEIGHT

Using 6" Downrod

- Distance of 16.5"
- Distance of 11.5"

GENERAL SPECS

3 Finishes Available
Lifetime Motor Warranty
Ten ABS Blades
52" Blade Sweep
30-Degree Blade Pitch
80" Lead Wire
6" Downrod Included
ETL Damp Listed

MECHANICAL SPECS

DC-165M Motor
6 Speeds-Reversible w/ Wall Control
6 Poles
.33/.22/.16/.09/.06/.04 AMPS on H/M/L
26/17/12/9/5/3 WATTS on H/M/L
84/74/62/51/41/30 RPMS on H/M/L
Light Kit Adaptable
Remote Control Included
Not Hugger Adaptable
Not Slope Ceiling Kit Adaptable
Maximum 25° Slope with Minimum 18" Downrod
Maximum Length Optional Downrod 48"

ENERGY SPECS

Energy Information at High Speed
Airflow: 2445 Cubic Feet/Minute
Electricity Use: 20 Watts (Excludes Lights)
Airflow Efficiency: 122 Cubic Feet/Minute/Watt
Visit QuorumInternational.com for DOE Energy Guide

REMOTE CONTROL



Included

INSTALLATION NOTE

Multiple fans installed on the same circuit require individual wall controls and switch legs. The power supply wire from the control to the fans can not be shared.

LIGHT KIT OPTIONS

Additional Light Kit options on page 232

201 Railhead Road, Fort Worth, TX 76106 - Tel. (817) 626-5483 - www.QuorumInternational.com

Please be advised that all information shown here is subject to verification by Quorum. In the event of a discrepancy, we reserve the right to make any corrections necessary.