
# uorum



# Windmill 72-in Galvanized Indoor/ **Outdoor Ceiling Fan (15-Blade)**

197215-9



## **FAN HEIGHT**

Using 8" Downrod • Distance of 18.5" ODistance of 13.5"

# **GENERAL SPECS**

3 Finishes Available Lifetime Motor Warranty Fifteen ABS Blades 72" Blade Sweep 30-Degree Blade Pitch 80" Lead Wire 8" Downrod Included **ETL Damp Listed** 

#### **MECHANICAL SPECS**

DC-165L Motor 6 Speeds-Reversible w/ Wall Control

.41/.27/.18/.14/.10/.07 AMPS on H/M/L

32/21/13/10/6/4 WATTS on H/M/L 53/49/41/44/29/23 RPMS on H/M/L

Light Kit Adaptable Remote Control Included

Not Hugger Adaptable

Not Slope Ceiling Kit Adaptable

Maximum 25° Slope with Minimum 18" Downrod Maximum Length Optional Downrod 48"

## **ENERGY SPECS**

Energy Information at High Speed Airflow: 2807 Cubic Feet/Minute Electricity Use: 35 Watts (Excludes Lights) Airflow Efficiency: 80 Cubic Feet/Minute/Watt Visit QuorumInternational.com for DOE Energy Guide

#### REMOTE CONTROL



Included

#### **INSTALLATION NOTE**

Multiple fans installed on the same circuit require individual wall controls and switch legs. The power supply wire from the control to the fans can not be shared.

# **LIGHT KIT OPTIONS**

Additional Light Kit options on page 232